

PAHOS

THE UNORTHODOX APPROACH

INPOIREMIX_{MKII}





There is no better way to listen to music

InPol (Inseguitore Pompa Lineare - Linear Pump Follower) is a system patented by Pathos Acoustics which has enjoyed great success and won many awards. Inpol devices have a special sonic personality obtainable only by means of this particular circuit design - fully balanced in Class A using a single solid state component in follower configuration, with high current gain and with voltage gain together. The valve amplifier amplifies the input signal voltage and InPol supplies the current to drive the loudspeakers without any further amplification. In this way the signal is entrusted to the valves and becomes a true copy of the original, with all the quality, purity and harmonic content of the original.

This technology allows an increase in the theoretical output in pure Class A of between 25% and 50% together with a low output impedance which is fundamental for the damping factor, and further improved by the double InPol.

InPolRemix MkII is a fully-balanced pure Class A integrated amplifier using the latest generation double-InPol circuitry.

The digital bias/gain set technology with intelligent control is entrusted to the same microprocessor which regulates the volume, thus guaranteeing the performance of the amplifier itself and its ability to drive the loudspeakers efficiently.

PAHOS





INPOIREMIXMKII



Thanks to the (optional) HiDac EVO converter, music lovers who want the best from the latest digital sources - controlled via smartphone or tablet App - will find their demands fully met. The elegant appearance design inherited from the ClassicRemix, with its compact dimensions make this a piece of audio equipment unique in its class. The central part of the chassis is carefully finished, while the lateral heatsinks, shaped to form the maker's logo, make a strikingly attractive statement and serve to highlight the carefully protected valves placed in the centre

InPolRemix MkII is available in various colours and personal choices of finish.

of the chassis.

InPolRemix raises the musical listening experience to the highest level, thanks to Pathos' audio design and engineering, and the use of components of the highest quality.



PAHOS

Pathos Acoustics Via Palù n. 50/52 36040 Grumolo delle Abbadesse Italy www.pathosacoustics.com

THE UNORTHODOX APPROACH

The manufacturer reserves the right to introduce technical and external modifications without prior notice. Pathos® is a registered trademark. Copyright Pathos Acoustics. All Rigths reserved.



Technical specifications:

Stereo integrated amplifier Pure class A Type:

- double INPOL technology - fully balanced -

digital Bias/gain set technology 2 x 25W@ 8 Ohm, 2 x 38W@ 4 Ohm

Output power:

 $2Hz - 150KHz \pm 0.5db$ Frequency response:

Input sensitivity: 470mVRMS Input impedance: 47KOhm

Output polarity: Selectable by remote control

Volume regulator: 2 x Burr Brown PGA2310 (180 steps 0,5dB)

THD: 0,1% @ 25W S/N Ratio: > 100dB

31 db Unbalanced 37 db Balanced Gain

Output impedance 0,9Ω

Connections:

1 Balanced XRL line, 4 unbalanced RCA line Analog inputs: Digital inputs: Installation of (optional) HiDac EVO board is

required to enable these inputs

1 USB port type "B", 1 SPDIF coaxial, 1 SPDIF optical

1 Ethernet RJ45, 2 USB port type "A"

Outputs: 1 Pre out stereo line RCA

1 Pre out stereo line Balanced XLR Pre-output phase can be selected 1 connector for jack headphone 6,3mm

Headphone Specifications:

Output power: 2,65W @ 32 Ω Output impedance: 0,45Ω 9,6 VRMS Max output level:

 $2Hz - 400KHz \pm 0,5db$ Frequency response:

THD: 0,025%

Dimensions:

Amplifier 370mm (D) x 280mm (W) x 180mm (H)

Net Weight 13,5Kg